

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 7/00		A1	(11) International Publication Number: WO 99/38311
			(43) International Publication Date: 29 July 1999 (29.07.99)
(21) International Application Number: PCT/US99/01631			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 27 January 1999 (27.01.99)			
(30) Priority Data: 60/072,649 27 January 1998 (27.01.98) US			
(71) Applicant (for all designated States except US): THOMSON CONSUMER ELECTRONICS, INC. [US/US]; 10330 North Meridian Street, Indianapolis, IN 46290 (US).			
(72) Inventors; and (75) Inventors/Applicants (for US only): RHODES, Robert, Andrew [US/US]; 13261 Arden Court, Carmel, IN 46033 (US). RAMASWAMY, Kumar [IN/US]; 9417B College Drive, Indianapolis, IN 46240 (US). KNUTSON, Paul, Gothard [US/US]; 148 South Emerson Avenue, Indianapolis, IN 46219 (US).			
(74) Agents: TRIPOLI, Joseph, S. et al.; Thomson Multimedia Licensing Incorporated, P.O. Box 5312, Princeton, NJ 08540 (US).			Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: SYSTEM AND METHOD FOR PROVIDING IP/INTERNET TELEPHONY



(57) Abstract

A system and method are described providing a wireless interface to an Internet Protocol (IP)/Internet telephony system. A wireless connection via the unregulated 900 MHz cordless phone spectrum or other spectrum allocated for wireless communications provides an RF link between an IP connection device, a network interface box or set-top box, and one or more wireless handsets. A processing/control element in the network interface box runs the required IP protocols to establish and manage call set-up and teardown, translate the digital voice signal between IP and the local RF link protocol, and provide the RF base station function for the handset(s). Each handset would incorporate the other end of the RF link. The wireless interface to a telephone handset may be through a settop box that is tied into a cable network such as a hybrid coaxial cable network. A protocol such as the Internet Protocol may be used to maintain a digital connection into a cable network while using an RF link to transmit compressed voice/data information between a telephone device such as a telephone handset and an interface unit such as a settop box.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

SYSTEM AND METHOD FOR PROVIDING IP/INTERNET TELEPHONY

FIELD OF THE INVENTION

5

The present invention generally relates to a system and method for providing internet telephony. In particular, the present invention relates to a system and method of providing a wireless internet telephone system over either a regular dial up telephone or a cable network.

10

BACKGROUND

One of the primary reasons for interest in offering Internet Protocol (IP)/internet telephony services is the pricing structures currently in place for the data service, and voice service offered by telephone operators. Long distance voice service can be thought of as "demand data" service, where the user pays a premium for the instantaneous access to a 64 Kbps channel (voice grade channel in the US). Widely publicized, promotional type pricing for this service is on the order of \$.10 a minute. By contrast, data service offered by telephone operators, such as that offered for a T-1 connection (24 voice quality data lines, for a 1.544 Mbps connection) is priced at approximately \$1000/month, which works out to \$.001 a minute per voice line. In the very near future, cable operators will place extreme pressure on even the data service rates for telephone operators, as cable modem will allow cable operators to offer hundreds of Kbps effective throughput for approximately \$50/month.

The basic idea of IP/internet voice telephony is to digitize your voice as you talk on the phone and send the digitized data as IP packets to the Internet. An IP voice device can be embedded within an Internet connection device such as a modem, a set-top-box, or a computer. It can be also built as a stand alone product. The stand alone IP voice device, for example, may provide an Ethernet jack which can be connected with an Internet connection device and other LAN devices. The IP voice device may also include interfaces to connect regular phone handsets. The quality of speech heard through a normal telephone line requires 64kb/s bandwidth. However, most current internet connections have less bandwidth, such as 28.8 Kbps, or 56 Kbps modem. Furthermore, even if a fast connection device is

used, such as an ISDN, or Cable Modem, the Internet network itself is a shared medium and has limited bandwidth. Therefore, audio codecs are usually embedded to compress the voice data.

To guarantee the interoperability between IP voice devices from 5 different vendors, the International Telecommunications Union (ITU) developed H.323 as the standard for telephony over IP network. H.323 defines common procedures for call setup, data compression, and data transport.

In a general sense, IP telephony can be thought of as providing a 10 "virtual" point to point connection for voice services over Internet. An IP voice device is basically a gateway to connect the regular telephone system to the Internet. The following example demonstrates how a call would be placed. A user in Indianapolis wants to call a friend in Paris. He picks up his IP voice device handset (or activates a virtual 15 handset on a computer screen for a "built-in" version) and hears a dial-tone like a regular telephone dial-tone. Then, he dials his friend's Paris phone number. The call travels over the Internet to some Switching Server provided by the IP telephony service provider. The Switching Server will connect the call to his friend's IP voice device 20 and initiates the call. If his friend has only a regular telephone, the Switching Server will connect the call to a gateway in Paris. The gateway in Paris then initiates a call over the public switched telephone network (PSTN) to the local Paris number. The cost to make phone calls between Indianapolis and Paris using two IP voice devices 25 is only the Internet access fee. If one party uses a regular telephone, the extra charge is merely that of a local dial call.

Depending on the Internet connection, there are at least two methods for making calls using an IP voice device: dial-up connections, and direct connections. With a dial-up connection, a user first calls an ISP 30 (Internet service provider) over a regular dial-up line to set up an Internet connection. Then, he will use the IP voice device handset to dial the phone number of the person he is calling. The present applicants recognize one problem with this approach is that the recipient must be online waiting for the call. So, the sender may have to first call the 35 recipient using a regular phone to make the appointment. With a direct connection, a user places a call using the IP voice device just as he does with the regular telephone. The direct connection indicates a permanent open channel to the Internet such as ISDN, or a cable access device. For a

dial-up connection call, a phone that has been called won't ring unless the Internet connection is already established for this phone. For a direct connection call, a phone would ring like a normal telephone.

The are many advantages to IP/Internet telephony. One such
5 advantage is reduced cost as described above. A low bit rate audio codec embedded in the IP voice device enables voice calls over a 28.8 Kbps modem. For a small reduction in voice quality, a person's monthly phone bill will be greatly reduced. If IP voice device used together with a cable
10 modem, the private service network plus high bandwidth of the cable modem will provide very good sound quality. Even if the voice quality provided by a IP/internet voice device is unsuitable for all phone communications, a IP/internet voice device may be useful as a second-line residential phone. Also, the H.323 standard supports several well defined conference modes and, therefore, IP voice device is able to be
15 used for multi-point conference calls. A "Web" dial-in service is advantageous for technical or customer support lines because, for example, an Internet address of a company's IP voice device can be embedded in the company's Web page and customers can then call the company simply by "clicking on" that Internet address. The cost
20 associated with toll-free ("800" number) telephone numbers will be reduced as a result.

In addition, MSOs (cable television system operators) have recently become interested in adding inexpensive telephony services using a combination of an MSO's private HFC (Hybrid Fiber Coax) network and the
25 public Internet. Voice signals are converted to digital values and transported across the networks using various established and proposed Internet protocols as IP (internet protocol) packets.

However, there are also problems associated with existing IP/Internet telephony systems. For example, the above-described
30 systems involve some combination of additional or revised POTS (Plain Old Telephone System) wiring, additional or revised cable network wiring, or additional network interface boxes. In addition, any connection which replaces a PSTN (public switched telephone network) service (such as reuse of the existing POTS wiring within the home to replace PSTN
35 services with HFC telephony services) may be required to supply so called "life-line" services. Some of these options require professional installation which may be costly, time consuming, and inconvenient for the user.

SUMMARY OF THE INVENTION

The invention resides, in part, in recognition of the above-described problems and, in part, in providing a system and method for solving these
5 problems. In particular, the inventors recognize that the described problems are solved by providing a voice call over an Internet connection by receiving a signal modulated in a first format and representing internet protocol data packets of the voice call; demodulating the signal modulated in the first format; modulating the demodulated signal into a
10 second format; transmitting the signal modulated in the second format via a wireless connection to a receiving device; and demodulating the signal modulated in the second format in the receiving device to complete the voice call.

An aspect of the present invention involves providing an internet
15 telephony system using a wireless connection such as via the unregulated 900 MHz cordless phone spectrum or other spectrum allocated for wireless communications to provide an RF link between an IP connection device, a network interface box or set-top box; and one or more wireless handsets. A processing/control element in the network interface box
20 would run the required IP protocols to establish and manage call set-up and teardown (currently defined within ITU-T H.323), translate the digital voice signal between IP and the local RF link protocol, and provide the RF base station function for the handset(s). Each handset would incorporate the other end of the RF link, and A/D and D/A functions to
25 convert the voice signal to and from digital packets, and potentially apply some compression algorithm to improve bandwidth utilization. In a handset design which does not incorporate enough processing power to perform the compression function, this function could potentially reside in the network interface box.

30 Another aspect of the present invention involves a mechanism to establish a wireless interface to a telephone handset through a settop box that is tied into a cable network such as a hybrid coaxial cable network.

Another aspect of the present invention involves using a standard protocol such as the Internet Protocol to maintain a digital connection into
35 a cable network while using an RF link to transmit compressed voice/data information between a telephone device such as a telephone handset and an interface unit such as a settop box.

Aspects of the present invention also involve providing for eliminating the need to add wiring, such as POTS wiring, to accommodate one or more handsets, or alternatively eliminating the need to add multiple cable drops and adapters such as POTS/HFC adapters. A wireless feature in accordance with aspects of the invention provides for coupling a network interface box to an existing cable outlet and for adding handsets as required without installation of additional outlets. In addition, aspects of the invention provide for multi-line Internet phone calls without rewiring. Another aspect of the invention involves adding an analog trunk interface wherein an IP voice device can be connected to a PBX device for providing an Internet PBX. For example, a user could dial a prefix, such as "9" to make a regular outside phone call, or dial a different prefix, such as "8" to make an Internet phone call.

In accordance with another aspect of the present invention, an IP voice device or a set top box provides for connecting to external equipment, such as a PC or Workstation, and utilization of computation power of external devices for providing additional features such as IP FAX service or video conferencing.

BRIEF DESCRIPTION OF THE DRAWING

The invention may be better understood by referring to the accompanying drawing in which:

Figure 1 shows, in block diagram form, an embodiment of a system incorporating aspects of the invention; and

Figures 2 through 7 show, in block diagram form, embodiments of portions of the system shown in Figure 1.

Figure 8 is a flow chart illustrating a method of operation according to the principles of the present invention.

DETAILED DESCRIPTION

In Figure 1, a system constructed in accordance with aspects of the invention comprises a PSTN network and a cable network coupled to a cable modem termination system. The PSTN Network and/or Cable Network provide alternative paths for coupling the system shown to the Internet, e.g., to an Internet service provider (ISP). The cable modem termination system is coupled to a gateway, such as in a home

environment, that comprises a cable modem network interface and first and second codecs for coupling to a conventional wired telephone via a subscriber line interface unit and/or to a wireless telephone unit via an RF modem interface, respectively.

5 Data transmission between the various units shown in Figure 1 occurs as follows. Data transmission between the PSTN network and the cable modem termination system shown in Figure 1 (path 1 in Figure 1) may occur in 64 Kbps/voice line format or in T1 or higher hierarchy. Data in the cable network (e.g., path 2 between the cable network and the
10 cable modem termination system in Figure 1, or path 2 between the cable modem termination system and the cable modem network interface unit in the gateway in Figure 1) may be carried over TCP/IP compressed at various rates or uncompressed linear at 64 Kbps/voice line. Data transmission between the cable modem network interface and the first
15 codec (path 3 in Figure 1) may occur in linear PCM format at 64 Kbps/voice line. Data transmission between the cable modem network interface and the second codec (path 4 in Figure 1) may occur in linear format at 64 Kbps/voice line or compressed at various rates. Data communication on path 5 in Figure 1 (between the first codec and the
20 subscriber line interface unit) may be in companded format at 64 Kbps/voice line. Data communication via path 6 in Figure 1 (between the second codec and the RF modem interface) may be in linear format at 64 Kbps/voice line or in compressed format at various rates. Data communicated to and from the subscriber line interface unit (path 7 in
25 Figure 1) may occur in analog format (e.g., for an RJ11 connector) and data communicated to and from the RF modem interface (path 8 in Figure 1) may occur in RF digital modulation format.

In embodiments shown in Figs. 2 and 3, IP telephony compression algorithms, call setup, and a cordless telephone adapter are incorporated
30 into an IP connection device or a client server. An example of an embodiment of such a device is a device referred to as a Network Computer (NC) which is a computer similar to a personal computer (PC) that is intended primarily for providing an interface to the Internet. That is, a network computer is intended primarily to provide computing power
35 and features sufficient, for example, to connect to the internet, execute web browser software and provide email capability. A cordless telephone adapter in accordance with aspects of the invention would allow the convenience to call from any room in a house without expensive rewiring.

The phone would ring only when there is an incoming IP phone call, and would present dial tone, etc. when used to place a call.

Two exemplary embodiments of an IP connection device having a cordless phone interface are shown in Figures 2 and 3. The system shown in Figure 2 utilizes an analog cordless telephone interface such as CT-1 (46/49 MHz). The system shown in Figure 3 utilizes a digital 900 MHz spread spectrum cordless telephone interface. The analog cordless IP voice device may provide a lower cost solution. However, a digital 900 MHz cordless IP voice device may be more advantageous in terms of voice quality and expandability. For example, a digital cordless phone typically provides better voice quality due to the noise cancelling capability of the digital system and a digital cordless IP voice device may have more than one handset. Also, a cordless IP voice device such as that shown in Figure 2 and/or 3 may be used for data service when used together with wireless modem.

The systems shown in Figures 2 and 3 may include a voice codec for compressing and decompressing the voice data if the modem of the IP connection device is running at low speeds. Table 1 lists some popular standard voice codec algorithms and their associated data rates.

Standard	Data Rate
G.711	64 kbps
G.723.1	5.3/6.3 kbps
G.728	16 kbps
G.729	8 kbps
GSM	13.3 kbps

Table 1 Voice compression standards

25

Figure 2 shows a client server device including IP voice features which, for example, may be included on an IP voice adapter card included in the client server device. The IP voice feature includes a CT-1 subsystem comprising RF transmitter circuitry Tx and receiver circuitry Rx, a programmable PLL synthesizer, a baseband (audio) processor, and a microprocessor interface. The components Tx and Rx and the PLL synthesizer are used to modulate and demodulate RF signals for transmission and reception of the wireless telephone signals. A duplexer is used to separate the transmit and receive paths

of the RF communications. As discussed before, a PCM codec integrated with filters may be needed to provide A/D and D/A conversions and compression, as well as the transmit and receive filtering of the signals. The digital signal processing (DSP) unit may be, for example, an integrated circuit (IC) that implements the voice codec under the control of the CPU (central processing unit) which may be a microprocessor. The CPU provides the central control of the wireless IP interface device shown in Fig. 2. The CPU is connected to the various components of the device via a data control bus. The CPU has a built in memory for storing the required control codes, including implementation of the H.323 standards and the TCP/UDP/IP protocols.

Figure 3 shows another exemplary IP connection device having a digital cordless phone interface such as a 900 Mhz interface. A baseband device usually includes a spread-spectrum modem, an audio engine (PCM, DTMF, etc.), a voice codec, and a microcontroller. The components Tx and Rx and the PLL synthesizer are used to modulate and demodulate RF signals for transmission and reception of the wireless telephone signals, to and from the wireless handset. A duplexer is used to separate the transmit and receive paths of the RF communications. A DSP unit is used to implement the voice codec under the control of the CPU. The CPU, or central processor, provides the central control of the wireless IP interface device as shown in Fig. 3. The CPU is connected to the various components of the device via a data control bus. The CPU has a built in memory for storing the required control codes, including implementation of the H.323 standards and the TCP/UDP/IP protocols.

Another aspect of the present invention is a wireless internet telephony system to be connected to a cable network. A network architecture in accordance with the principles of the present invention is shown in Figure 4.

In Figure 4, an interface to cable network(100) comprises a cable modem termination in the physical layer that has a bi-directional channel connected to the hybrid fiber coax network (105). The physical layer modulation scheme may comprise, for example, Quadrature Amplitude Modulation (QAM). The transport mechanism may comprise TCP/IP. In order to enable the voice application over the cable modem, the network interface unit may employ a protocol such as H.323 over TCP/IP. This enables signaling, call set up and other functions. The voice (fax and

analog modem is included in this paradigm) data itself may be carried in a compressed or uncompressed format. For example, companded voice data at 64 Kbps can be carried over the cable network embedded in TCP/IP packets. Alternatively, it may be compressed using one of many voice compression methods and carried over the cable network embedded in TCP/IP packets. Certain types of data cannot be compressed (example fax or analog modem) and need to be carried in a linear format.

Figure 4 also depicts a wireless interface (104) to a plurality of handsets or receiver devices (101, 102, 103...). The protocol between the base device (100) and the handsets may be entirely proprietary or some standard interface. Additionally, the data format or voice (compressed in one of many possible algorithms or uncompressed) may be different in the RF network as compared to the format in which the voice was carried over the HFC network.

Advantages associated with maintaining the same data format (e.g., compression scheme) in the wired (cable) and wireless network are:

1. only a single encoding/decoding process is necessary which, in a home environment, can take place at the wireless handset or mobile terminal (multiple transcoding processes normally result in degradation of the original source material); and
2. the base station (e.g., in the home) is transparent to the data from the handset or mobile terminal.

An advantage associated with maintaining different data formats (e.g., compression scheme) in the wired (cable) and wireless network is that certain compressed formats are specifically suited to be carried over certain transmission channels. Channel errors, depending on how they occur, can cause different degradation to the source material depending on the compression scheme that is employed. The wired and wireless environments are very different in terms of channel characteristics. Therefore, tailoring the coding scheme to match the characteristics of the channels may have some benefits in the overall system design.

Figure 5 shows further details of an exemplary embodiment of cable set-top box (100) in Figure 4. The cable channel (91) that carries both downstream and upstream data is usually frequency division multiplexed to enable simultaneous channels of operation. Further, within a specific channel, due to the nature of the shared cable medium.

multiple users may signal using a time division multiplexed access mechanism. This task is coordinated by the head end.

The cable interface (40) is a network interface unit (NIU) comprising of a modulator/demodulator pair and a processing unit for interpreting the incoming data stream and messages. One of the transport mechanisms employed is TCP/IP. The NIU receives data, demodulates decodes and extracts the information pertaining to specific voice channels in this application. It is also responsible for maintaining signaling information with the external network (for example using the H.323 protocol stack or any other commonly used signaling stack used in telephony). Additional features such as caller ID, messaging, voice mail etc. are features that are supported by the NIU. This is enabled by its interface with the Caller ID block (50), the external digital signal processor (10) with an embedded microprocessor (5) that coordinates the task of messaging, and voice compression/decompression as necessary.

The incoming messages are stored in compressed or uncompressed format in the message memory(60). Other system architectures may be used wherein the messages are stored in message memory in yet another compressed format to increase the time over which messages can be stored in a given amount of available memory. This task of additional compression/decompression may take place in DSP unit 10. The code memory (70) contains the code for the DSP engine. The RF cordless circuitry (20) is responsible for communicating with the handsets or mobile terminals and exchange specific information intended for each device. In addition to the exchange of data, 20 is also responsible for exchanging signaling and status information. The system shown in Figure 5 includes a common bus (80) between the functional components for data exchange, but a generalized architecture need not be limited to the bus structure shown in Figure 5. Additionally, messaging information and caller ID information are exchanged between 100 and the handsets or mobile terminals through the RF/cordless circuitry.

Figure 6 shows an exemplary embodiment of the receiver/set-top box 100 described earlier in regard to Figure 4 and referred to as unit 700 in regard to Figure 6. The transmit and receive signals into the cable network through the RF connector (796) are kept isolated using a diplexer (795). The cable tuner (705) and demodulator(710) convert the digitally modulated signal (for example QAM) into a composite digital bit stream which is delivered to a Medium Access Control - MAC (720) block

that performs the task of separating information into logical transport streams. Additionally, unit 720 is responsible for synchronizing with the cable head end in order to provide the settop box access control to the common cable medium for return channel information. The burst
5 modulator (740) and power amplifier(730) create and send data in the return channel path back into the cable network.

The RF processing chain for processing the digital information from the cable network starts with the interface, or input/output (I/O) unit (760) which may be implemented as an application specific integrated
10 circuit (ASIC) and which interfaces with a cordless phone processing unit (750), that also may be part of an ASIC or a separate ASIC, to create individual links with handsets or mobile receivers. Unit 750 is coupled to memory units DRAM 765 and ROM 770 for receiving stored processing instructions and for temporary data storage during processing. The data
15 intended for each individual handset or mobile receiver may be time slotted, modulated and sent on the RF link through the RF connector (797). Additional information streams processed by the MAC processing block (720) may be directed to an ethernet port (783) through an ethernet controller (781) or an USB (Universal Serial Bus) port (784)
20 through an USB controller (785) or an RS232 interface (791) through an RS232 driver(790).

The various functions shown in Figure 6 are connected to bus 721 for communication of data and control information between the functions and between the functions and CPU 786 which controls the operation of
25 the functions in device 700. Also coupled to bus 721 are memory units 775 and 780 for storing control programs and data for CPU 786 and other functions in device 700. Power for unit 700 is provided by power supply 792. Also, while many of the processing blocks shown in Figure 6 may be optional depending on the specific application or product, the system
30 shown in Figure 6 illustrates the composite nature of the data coming over the cable system. The path for the voice channels are of particular interest in regard to the present invention.

Fig. 7 shows a block diagram of an implementation of a wireless handset 101. The handset 101 comprises a DSP unit 201 including a
35 microprocessor 210, a speaker, earpiece, RF circuitry and a keypad. The microprocessor 210 controls the various components of the wireless handset 101 via a system bus 202. The RF circuitry is connected to a RF antenna for transmitting and receiving RF wireless signals. A keypad 204

is used for an user to dial a phone number and for controlling other functions of the wireless phone. The DSP converts the analog signal into a digital signal to be transmitted over the RF spectrum if a digital transmission system is used. Memory 203 stores the program codes to be
5 executed by the microprocessor 210.

It is to be understood that the embodiments and variations shown and described herein are illustrations only and that various modifications may be implemented by those skilled in the art without departing from the scope and spirit of the invention.

10

Figure 8 shows a flow chart illustrating a method of operation according to the principles of the present invention. At step 802, a signal is received by, for example, by the cable interface 40 of unit 100. This signal is demodulated by cable interface 40 into a demodulated signal at
15 step 803. The unit may decide to further compress or decompress this demodulated signal under the control of the DSP unit 10 as described before. The DSP then causes this signal to be further modulated at step 805 by the RF/Cordless circuitry 20. This further modulated signal is then transmitted wirelessly to a wireless unit, for example, as shown in
20 Fig. 7. After receiving this further modulated signal at the wireless unit, the wireless unit then demodulates this signal for completion of the IP voice call.

It is to be understood that the embodiments and variations shown
25 and described herein are illustrations only and that various modifications may be implemented by those skilled in the art without departing from the scope and spirit of the invention.

30

CLAIMS

1. A method for processing a voice call over an internet, comprising the steps of:
 - 5 receiving a signal modulated in a first format, said signal representing internet protocol data packets of said voice call;
 - demodulating said signal modulated in said first format;
 - 10 modulating said demodulated signal into a second format;
 - transmitting wirelessly said signal modulated in said second format to a wireless device; and
 - 15 demodulating said signal modulated in said second format in said wireless device.
2. The method of claim 1 further comprising the step of:
 - 20 compressing said demodulated signal modulated in said first format before said transmitting step.
3. The method of claim 1 further comprising the step of:
 - 25 decompressing said demodulated signal modulated in said first format before said transmitting step.
4. The method of claim 2 further comprising the step of: decompressing said demodulated signal modulated in said second format in said wireless device after said demodulating step in said wireless device.
- 30 5. The method of claim 1 wherein said first format is H.323 compliant.
6. The method of claim 1 wherein the first format comprises same modulation scheme as the second format.
- 35 7. The method of claim 1 wherein the first format comprises a different modulation scheme as the second format.
8. A system for processing a voice call over an internet, comprising:
 - 40 means for receiving and demodulating a signal modulated in a first format, said signal representing internet protocol data packets of said voice call;
 - 45 means for modulating said signal into a second format for wireless transmission to a wireless device; and

said wireless device further comprising means for demodulating said signal in said second format for completion of said voice call.

5 9. The system of claim 8 wherein said first format is H.323 compliant.

10. The system of claim 8 wherein said system further comprising means for compressing said demodulated signal modulated in said first format before said wireless transmission.

10

11. The system of claim 8 wherein said system further comprising means for decompressing said demodulated signal modulated in said first format before said wireless transmission.

15 12. The system of claim 10 wherein said system further comprising means for decompressing said compressed signal in said wireless device.

13. The system of claim 8 wherein the first format comprises same modulation scheme as the second format.

20

14. The method of claim 8 wherein the first format comprises a different modulation scheme as the second format.

25

1/6




FIG. 1




FIG. 2

2/6




FIG. 3




FIG. 4

3/6




FIG. 5

4/6




FIG. 6

5/6




FIG. 7

6/6




FIG. 8

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/01631

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04M7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 28628 A (LABS OF ADVANCED TECHNOLOGIES) 7 August 1997 see page 11, paragraph 1 - paragraph 3 see page 13, paragraph 3 see page 14, paragraph 1 - page 16, paragraph 4 see page 25, paragraph 3 - page 27, paragraph 2 ---	1-4,6-8, 10-14
A	WO 97 29581 A (LINK WORLDWIDE INC I) 14 August 1997 see abstract see page 15, line 18 - page 16, line 20 --- -/-	1-4,6-8, 10-14



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

11 May 1999

Date of mailing of the international search report

21/05/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Megalou, M

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/01631

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	MOFFAT I G ET AL: "THE INTERNET TELEPHONE - A NEW PARADIGM" IEEE COLLOQUIUM ON ADVANCES IN INTERACTIVE VOICE TECHNOLOGIES FOR TELECOMMUNICATION SERVICES, 12 June 1997, pages 10/1-10/06, XP000197765 see the whole document ----	1-14
A	CHEN R -X ET AL: "AN I-PHONE SYSTEM DESIGN AND IMPLEMENTATION WITH A PORTABLE SPEECH CODING COPROCESSOR" IEEE TRANSACTIONS ON CONSUMER ELECTRONICS, vol. 43, no. 4, 1 November 1997, pages 1262-1269, XP000770882 see the whole document ----	1-14
P, X	WO 98 11703 A (SOLOMON YORAM ; SOLRAM ELECTRONICS LTD (IL)) 19 March 1998 see page 19, line 14 - page 20, line 6; figure 5 see page 34, line 4 - page 35, line 24 see figures 4, 6-8, 14A, B -----	1, 6, 8, 13

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/01631

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9728628 A	07-08-1997	AU 1851397 A	22-08-1997
WO 9729581 A	14-08-1997	AU 2251497 A	28-08-1997
		CA 2245815 A	14-08-1997
		EP 0878086 A	18-11-1998
WO 9811703 A	19-03-1998	AU 3951797 A	02-04-1998

This Page Blank (uspto)